

Why compromise, when you have a choice. Choose genuine. Say no to non-genuine.



Technical **Specifications**

| | MFC-B7715DW |
|--|---|
| Key Functions | Print, Scan, Copy, Fax and Automatic 2-sided Printing With Wireless Connectivity |
| PRINT FUNCTIONS | Thin, coar, copy, randraterialic 2 class randing that through coarse |
| Print Speed (A4/Letter) | Up to 34 / 36 ppm |
| 2-sided Printing | Yes |
| Print Resolution | 600 x 600 dpi; HQ1,200 (2,400 x 600 dpi) quality; 1,200 x 1,200 dpi |
| | Less than 8.5 secs |
| First Printout Time (Ready) Max. Monthly Duty Cycle | Up to 15,000 pages |
| COPY FUNCTIONS | Op to 13,000 pages |
| | H= t= 04/00 |
| Copy Speed (A4/Letter) | Up to 34/36 cpm |
| Reduction/Enlargement (%) | 25% - 400% in 1% increments |
| Copy Resolution (Glass - Optical) | 600 x 600 dpi |
| Copy Features | N in 1 |
| SCAN FUNCTIONS | |
| Scanning Speed (Mono/Colour)# | 22.5 / 7.5 ipm |
| Scan Resolution | Optical - 1,200 x 1,200 dpi; Interpolated 19,200 x 19,200 dpi |
| Scan to Features | SharePoint (PC-CC4 Only), Image, OCR, File, Email, FTP |
| FAX FUNCTIONS | |
| Modem Speed | 33,600bps (Fax), Super G3 |
| PC Fax (Send/ Receive)% | Yes / Yes (Windows only) |
| Speed & Group Dials | 200 locations / 20 Groups |
| Out of Paper Reception | Up to 400 pages |
| Out of Faper Reception | (ITU-T Test Chart, Standard Resolution, JBIG) |
| PAPER HANDLING | |
| Input Capacity | 250 sheets |
| Manual Feed Slot | 1 sheet |
| ADF Capacity | 50 Sheets |
| Output Capacity [^] | 120 Sheets Face Down |
| Media Weights | 60 to 230g/m² (Using Manual Feed Slot) |
| Media Size | A4, Letter, A5, A5(Long Edge), A6, Executive, Legal, Folio, Mexico Legal, India Legal |
| CONNECTIVITY | |
| Interface | Hi-Speed USB 2.0, 10Base-T/100Base-TX, IEEE 802.11b/g/n (Infrastructure Mode), IEEE 802.11g/n (Wi-Fi Direct) |
| Mobile Solutions | AirPrint (Print & Scan), Mopria (Print), Google Cloud Print, Brother iPrint&Scan |
| Wi-Fi Direct | Yes |
| OTHERS | |
| Processor Speed | 600MHz |
| Memory | 128MB |
| Emulation | PCL6, BR-Script3, PDF Version 1.7 |
| Display | 16 characters x 2 lines |
| OS Compatibility | Windows 7 SP1, 8, 8.1, 10, Server 2008 (Network only), Server 2008 R2 (Network only), Server 2012 (Network only), Server 2012 R2 (Network only), 10, Server 2016 (Network only), macOS v10.10.5, 10.11.x 10.12.x (Download only), CUPS, LPD/LPRng (x86/x64 environment) |
| Utilities & Solutions | BRAdmin Light: Windows (by Download); BRAdmin Pro3: Windows (by Download) |
| Energy Saving Mode | Energy Star |
| Power Consumption (Printing / Sleep) | 475W / 6.2W |
| Power Source | 220-240V, AC 50/60Hz |
| Noise Level | LpAm = 49 dB(A) |
| SUPPLIES | |
| Standard Yield Toner (TN-B021)* | Approx. 2,600 Pages |
| | ··· |
| Drum (DR-B021) | Approx. 12,000 Pages |
| Inbox Toner | Approx. 2,600 Pages |
| DIMESIONS & WEIGHT | |
| Dimension (W x D X H) | 410 x 398.5 x 318.5 mm |
| Weight | 12kg |

[^]Actual output tray capacity may vary depending on environmental conditions *In accordance with ISO/IEC 19752







Brother strongly recommends the use of genuine Brother consumable brother strongly recommends the use of genuine Brother consumable products only. Benefits include better quality print, greater yields per consumable, protection of your machine from damages and achievement of optimum performance. As a precaution, please not that your machine warranty may not cover any damages arising from the use of non-genuine consumables.

